

Stafix® GRIP is a low-tack, PVC-free self-adhesive material that adheres to various clean and very smooth surfaces with a silicon adhesion layer.

STAFIX GRIP

Version 2024-1

Stafix® GRIP

Product datasheet

- For indoor and outdoor use
- Lifespan 12 months indoors, 6 months outdoors
- Working temperature -30 °C to 110 °C
- Glue and residue-free, washable, reusable, recyclable

Formats and printing compatibility

Material for printing test available upon request.

PRODUCT	PRINTING	APPEARANCE	SHEETS	REELS
Offset	Offset (traditional & UV)	White and clear	450 x 640 white 707 x 1000 white 707 x 1000 clear	
Large format	UV-inkjet, Latex, Eco-solvent, UV-LED, UV-gel	White and clear		1370 mm x 30 m 1370 mm x 100 m 610 mm x 5 m (Test reel)
Toner	Dry Toner, Laser	White and clear	320 x 450	
Indigo	HP® Indigo	White	320 x 460 530 x 750	

Recommended applications

- Suitable for glass – especially for fridges and freezers, store decoration and window display, events, exhibitions and trade show advertising.
- Ideal for uses such as window graphics, advertising for vending machines, beverages, food, ice cream, beauty and sports products.



Offset, Toner and Indigo product data



	OFFSET				TONER				INDIGO	
	White		Clear		White		Clear		White	
	Film	Liner	Film	Liner	Film	Liner	Film	Liner	Film	Liner
Weight (g/m ²)	135	45	155	70	150	70	180	70	110	45
Thickness (mm)	0.195	0.050	0.115	0.050	0.115	0.050	0.140	0.050	0.170	0.050
Total Weight (g/m ²)	180		225		220		250		155	
Total Thickness (mm)	0.245		0.165		0.165		0.190		0.220	
Film & Liner	PP		PET		PET		PET		PP	

Large format product data



LARGE FORMAT				
MATERIAL	White		Clear	
	Film	Liner	Film	Liner
Weight (g/m ²)	140	45	180	70
Thickness (µm)	190	50	140	50
Total Weight (g/m ²)	180		225	
Total Thickness (mm)	0.245		0.165	
REELS				
Reel Length (m)	30	100	30	100
Reel Width (mm)	1370		1370	
Reel Diameter, OD (mm)	128	196	120	177
Core (mm)	76,2 (3")		76,2 (3")	
Reel Weight (kg)	10	28	13	36
Film & Liner	PP		PET	

For expert printing tips and more, please visit Stafix website at www.stafix.eu

Important: All information concerning Stafix® products is based on current quality levels. Stafix Ltd. reserves the right to change the specifications of the contents as part of our continual product development. Before using the material, the end user must analyze the suitability of the material for the specific application. Stafix Ltd. does not assume liability for the unsuitable performance of the material.

Stafix Ltd
Konttisentie 8B
40800 Vaajakoski
Finland

info@stafix.fi
www.stafix.eu
VAT: FI20849407

Recyclability:

PP: Grade 5 plastic
PET: Grade 1 plastic

Shelf life:

24 months: Offset: Large format, Toner
18 months: Indigo

Usage:

Before applying the material, the surface must be clean, dry and grease-free.