

Stafix® PAPTIC is a wood-fiber-based, fully plastic- and PVC-free self-adhesive material that adheres to various clean and smooth surfaces with a removable, UV hot-melt adhesion layer.

STAFIX PAPTIC

Version 2024-1

Stafix® PAPTIC

Product datasheet

- For short and mid-term single use
- Lifespan average 3 months
- Effortless, bubble-free application
- Removable in one piece
- Residue-free, recyclable as paper

Formats and printing compatibility

Material for printing test available upon request.

PRODUCT	PRINTING	APPEARANCE	SHEETS	REELS
Sheets	Offset, Dry Toner	White	500 x 700 320 x 450	
Large Format	UV-inkjet, Latex, Eco-solvent*, UV-LED, UV-gel	White		1370 mm x 30 m 1370 mm x 100 m

\* Test color reproduction beforehand for ink absorption

Recommended applications

- Perfect for point-of-sale advertising, fast-moving campaigns, and quick turnover promotions.
- PAPTIC is ideal for businesses committed to sustainability and high-quality presentation, such as natural beauty and care brands, cosmetics, organic products, pharmacies, healthcare providers, events, trade shows, and exhibitions.
- Easy, bubble-free application and removal on smooth surfaces.



## Sheets product data



OFFSET



TONER

OFFSET, DRY TONER		
	White	
	Paptic Facestock	Backer
Weight (g/m <sup>2</sup> )	100	120
Thickness (mm)	0.160	0.150
Total Weight (g/m <sup>2</sup> )	220	
Total Thickness (mm)	0.310	
Facestock	PAPTIC	
Backer	Siliconized PE-coated paper backer	

## Large Format product data



UV-INKJET



LATEX



ECO-SOLVENT

UV-INKJET, LATEX, ECO-SOLVENT		
MATERIAL	White	
	Paptic Facestock	Backer
Weight (g/m <sup>2</sup> )	100	120
Thickness (mm)	0.160	0.150
Total Weight (g/m <sup>2</sup> )	220	
Total Thickness (mm)	0.310	
REELS		
Reel Length (m)	30	
Reel Width (mm)	1370	
Reel Diameter (cm)	14	
Core (mm)	76,2 (3")	
Reel Weight (kg)	12	
Facestock	PAPTIC	
Backer	Siliconized PE-coated paper backer	

For expert printing tips  
and more, please visit Stafix  
website at [www.stafix.eu](http://www.stafix.eu)

**Important:** All information concerning Stafix® products is based on current quality levels. Stafix Ltd. reserves the right to change the specifications of the contents as part of our continual product development. Before using the material, the end user must analyze the suitability of the material for the specific application. Stafix Ltd. does not assume liability for the unsuitable performance of the material.

Stafix Ltd  
Konttisentie 8B  
40800 Vaajakoski  
Finland

[info@stafix.fi](mailto:info@stafix.fi)  
[www.stafix.eu](http://www.stafix.eu)  
VAT: FI20849407

**Recyclability:**  
Facestock: Paper (including glue layer)

**Shelf life:**  
12 months, following storage guidelines

**Usage:**  
Before applying the material, the surface  
must be clean, dry and grease-free.