

Stafix® XTAC is a self-adhesive, synthetic paper-based, PVC-free material that adheres to various clean and smooth surfaces with a removable, UV hot-melt adhesion layer.

STAFIX XTAC

Version 2024-1

# Stafix® XTAC

## Product datasheet

- For Indoor and outdoor use
- Lifespan average 6 months for indoor and outdoor
- Printable with regular offset inks
- PVC- and residue-free, reusable, recyclable

### Formats and printing compatibility

Material for printing test available upon request.

| PRODUCT      | PRINTING  | APPEARANCE | SHEETS    | REELS     |
|--------------|---|------------|-----------|-----------|
| Offset       | Offset<br>(traditional & UV)                        | White      | 500 x 700 |           |
| Dry Toner    | Dry Toner, Laser                                    | White      | 320 x 450 |           |
| Large Format | UV-inkjet, Latex,<br>Eco-solvent,<br>UV-LED, UV-gel | White      |           | 1370 x 30 |

### Recommended applications

- Ideal for printers in offices and for temporary signage printing, as well as for temporary promotions and informative signs in locations such as restaurants.
- XTAC excels in creating removable window graphics, impactful in-store advertising, and enhancing glass freezer and cooler doors promotions.



## Sheets product data



| OFFSET                           |                                    |        | DRY TONER                          |        |
|----------------------------------|------------------------------------|--------|------------------------------------|--------|
| White                            |                                    |        | White                              |        |
|                                  | Film                               | Backer | Film                               | Backer |
| Weight (g/m <sup>2</sup> )       | 88                                 | 120    | 129                                | 120    |
| Thickness (mm)                   | 0.120                              | 0.150  | 0.125                              | 0.150  |
| Total Weight (g/m <sup>2</sup> ) | 208                                |        | 249                                |        |
| Total Thickness (mm)             | 0.270                              |        | 0.275                              |        |
| Film                             | PP                                 |        | PP                                 |        |
| Backer                           | Siliconized PE-coated paper backer |        | Siliconized PE-coated paper backer |        |

## Large Format product data



| UV-INKJET, LATEX, ECO-SOLVENT    |                                    |        |
|----------------------------------|------------------------------------|--------|
| MATERIAL                         | White                              |        |
|                                  | Film                               | Backer |
| Weight (g/m <sup>2</sup> )       | 88                                 | 120    |
| Thickness (mm)                   | 0.120                              | 0.150  |
| Total Weight (g/m <sup>2</sup> ) | 208                                |        |
| Total Thickness (mm)             | 0.270                              |        |
| REELS                            |                                    |        |
| Reel Length (m)                  | 30                                 |        |
| Reel Width (mm)                  | 1370                               |        |
| Reel Diameter (cm)               | 13.5                               |        |
| Core (mm)                        | 76,2 (3")                          |        |
| Reel Weight (kg)                 | 13                                 |        |
| Film                             | PP                                 |        |
| Backer                           | Siliconized PE-coated paper backer |        |

For expert printing tips and more, please visit Stafix website at [www.stafix.eu](http://www.stafix.eu)

**Important:** All information concerning Stafix® products is based on current quality levels. Stafix Ltd. reserves the right to change the specifications of the contents as part of our continual product development. Before using the material, the end user must analyze the suitability of the material for the specific application. Stafix Ltd. does not assume liability for the unsuitable performance of the material.

**Stafix Ltd**  
Konttisentie 8B  
40800 Vaajakoski  
Finland

[info@stafix.fi](mailto:info@stafix.fi)  
[www.stafix.eu](http://www.stafix.eu)  
VAT: FI20849407

**Recyclability:**  
PP: Grade 5 plastic

**Shelf life:**  
12 months

**Usage:**  
Before applying the material, the surface must be clean, dry and grease-free.