

Stafix® PULPO is a self-adhesive, PVC-free material that adheres bubble-free to smooth and semi-smooth surfaces with vacuum-structure adhesion layer.

# PULPO

Version 2025-1

## Stafix® PULPO

### Product datasheet

- For short and long-term indoor usage
- Thousands of micro-cavities ensure bubble and residue-free suction
- Lifespan average 3-12 months
- Effortless, low-tack application
- PVC-free. Reusable and recyclable

### Formats and printing compatibility

Material for printing test available upon request.

PRODUCT	PRINTING	APPEARANCE	MATERIAL	SHEETS	REELS
Sheets	Offset	White	PP	707 x 1000	
Sheets	Indigo	White	PP	320 x 460 530 x 750	
Large Format	UV-Inkjet, Eco-Solvent, Latex	White	PP		1370 mm x 30 m 1370 mm x 100 m

### Recommended applications

- Ideal for quick and easy installation on any clean, smooth or semi-smooth surface.
- Great for retail advertising, events and exhibitions requiring easy, bubble-free application, reuse and removal.
- Available in both sheets and large format, to suit a multitude of applications.



# Sheets product data



OFFSET			INDIGO	
White			White	
	Film	Backer	Film	Backer
Weight (g/m2)	145	40	130	45
Thickness (mm)	0.220	0.050	0.200	0.050
Total Weight (g/m2)	185		175	
Total Thickness (mm)	0.270		0.250	
Film	PP		PP	
Backer	PP		PP	

# Large Format product data



UV-INKJET, ECO-SOLVENT, LATEX		
MATERIAL	White	
	Film	Backer
Weight (g/m2)	145	79
Thickness (mm)	0.220	0.088
Total Weight (g/m2)	270	
Total Thickness (mm)	0.400	
REELS		
Reel Length (m)	30	100
Reel Width (mm)	137	
Film	PP	
Backer	PP	

For expert printing tips and more, please visit Stafix website at [www.stafix.eu](http://www.stafix.eu)

**Important:** All information concerning Stafix® products is based on current quality levels. Stafix Ltd. reserves the right to change the specifications of the contents as part of our continual product development. Before using the material, the end user must analyze the suitability of the material for the specific application. Stafix Ltd. does not assume liability for the unsuitable performance of the material.

**Stafix Ltd**  
 Konttisentie 88  
 40800 Vaajakoski  
 Finland  
[info@stafix.fi](mailto:info@stafix.fi)  
[www.stafix.eu](http://www.stafix.eu)  
 VAT: FI20849407

**Recyclability:**  
 PP: Grade 5 plastic

**Shelf life:**  
 12 months

**Usage:**  
 Before applying the material, the surface must be clean, dry and grease-free.