

Stafix® Magnet is a PVC free, pre-magnetized material that adheres to smooth iron or steel surfaces through magnetic charge.

STAFIX MAGNET

Version 2025-1

Stafix® MAGNET Product datasheet

- For short and mid-term usage
- Suited for smooth iron or steel surfaces
- Lifespan average 3-6 months
- Extremely easy to install and remove
- Glue- and residue-free, reusable

Formats and printing compatibility

Material for printing test available upon request.

PRODUCT	PRINTING	APPEARANCE	MATERIAL	SHEETS	PULL STRENGTH
Sheets Total thickness 0.330 mm	Offset, Dry Toner, Indigo	White	Paper	320 x 460 mm	6 g/cm²
Sheets Total thickness 0.360 mm	Offset, Indigo	White	Paper	530 x 750 mm	8 g/cm²
Sheets Total thickness 0.400 mm	Indigo	White	PP	320 x 460 mm 530 x 750 mm	10 g/cm²

Recommended applications

- Ideal for quick and easy installation on any smooth iron or steel surface.
- Great for retail advertising, events and exhibitions requiring excellent print quality, ease of application, reuse and removal.
- Available in both paper and PP, with PP being suitable for humid conditions.



Sheets product data (Paper)



	OFFSET, DRY TONER, INDIGO	OFFSET, INDIGO
MATERIAL	White	White
	Pre-magnetized paper	Pre-magnetized paper
Total Weight (g/m2)	740	820
Total Thickness (mm)	0.330	0.360
Material	Paper	Paper
Pole pitch (mm)	1.0	

Sheets product data (PP)



	INDIGO
MATERIAL	White
	Pre-magnetized PP
Total Weight (g/m2)	860
Total Thickness (mm)	0.400
Material	PP
Pole pitch (mm)	1.0

For expert printing tips and more, please visit Stafix website at www.stafix.eu

Important: All information concerning Stafix® products is based on current quality levels. Stafix Ltd. reserves the right to change the specifications of the contents as part of our continual product development. Before using the material, the end user must analyze the suitability of the material for the specific application. Stafix Ltd. does not assume liability for the unsuitable performance of the material.

Stafix Ltd
Konttisentie 8B
40800 Vaajakoski
Finland

info@stafix.fi
www.stafix.eu
VAT: FI20849407

Shelf life:

12 months (Store in the original packaging, protected from sunlight, at a temperature of 10 °C to 35 °C and a relative humidity of 20 % to 40 %.)

Usage:

Before applying the material, the surface must be clean, dry and grease-free.