

Stafix®PULPO is a self-adhesive, PVC-free material that adheres bubble-free to smooth and semi-smooth surfaces with vacuum-structure adhesion layer.

STAFIX PULPO

Version 2026-6

Stafix® PULPO Product datasheet

- For short and long-term indoor usage
- Thousands of micro-cavities ensure bubble and residue-free suction
- Lifespan average 3-12 months
- Effortless, low-tack application
- PVC-free. Reusable and recyclable

Formats and printing compatibility

Material for printing test available upon request.

PRODUCT	PRINTING	APPEARANCE	MATERIAL	SHEETS	REELS
Offset	Offset (traditional & UV)	White	PP	707 x 1000	
Indigo	HP® Indigo	White	PP	320 x 460 530 x 750	
Toner	Dry Toner, Laser	White	PET	320 x 450	
Large Format	UV-Inkjet, Eco-Solvent, Latex	White	PP		1370 mm x 30 m 1370 mm x 100 m 610 mm x 5 m (Test reel)

Recommended applications

- Ideal for quick and easy installation on any clean, smooth or semi-smooth surface.
- Great for retail advertising, events and exhibitions requiring easy, bubble-free application, reuse and removal.
- Available in both sheets and large format, to suit a multitude of applications.



Sheets product data



	OFFSET		INDIGO		DRY TONER	
MATERIAL	White		White		White	
	Film	Backer	Film	Backer	Film	Backer
Weight (g/m2)	145	40	115	40	170	105
Thickness (mm)	0.220	0.050	0.180	0.050	0.180	0.075
Total Weight (g/m2)	185		155		275	
Total Thickness (mm)	0.270		0.230		0.255	
Film & Liner	PP		PP		PET	

Large Format product data



UV-INKJET, ECO-SOLVENT, LATEX

MATERIAL	White	
	Film	Backer
Weight (g/m2)	145	80
Thickness (mm)	0.220	0.088
Total Weight (g/m2)	225	
Total Thickness (mm)	0.308	
REELS		
Reel Length (m)	30	100
Reel Width (mm)	1370	
Film & Liner	PP	

For expert printing tips and more, please visit Stafix website at www.stafix.eu

Important: All information concerning Stafix® products is based on current quality levels. Stafix Ltd. reserves the right to change the specifications of the contents as part of our continual product development. Before using the material, the end user must analyze the suitability of the material for the specific application. Stafix Ltd. does not assume liability for the unsuitable performance of the material.

Stafix Ltd
 Konttisentie 8B
 40800 Vaajakoski
 Finland
info@stafix.fi
www.stafix.eu
 VAT: FI20849407

Recyclability:
 PP: Grade 5 plastic

Shelf life:
 12 months

Usage:
 Before applying the material, the surface must be clean, dry and grease-free.